

**5R, 5RP**

美規, 玻璃管, 慢熔斷

UL 5x15mm Glass Slow Blow Fuse

**Sun Fuse**

RoHS

**Functional Characteristics 電氣特性**

Testing current 測試電流	Blow time limit 熔斷時間	
	Min 最小	Max 最大
100%	4 hour (小時)	-
135%	-	1 hour (小時)
200%	3 sec (秒)	10 sec (秒)

**Safety Approvals (安全認証)**

UL listed and certified for Canada from 125mA to 1A, 250V; 125mA to 5A, 125V.

UL recognized from 125mA to 5A, 250V.

**Marking (印字)**

Sun trademark, appropriate UL logo, "5R", current and voltage ratings are stamped on the fuse end caps.

**Material (材料)**

Fuse body – glass tube

End cap – nickel plated brass

Pigtail – tin plated copper on nickel plated brass cap

**Packing (包裝)**

- Bulk pack of 100pcs per box for 5R and 500pcs for 5RP.
- Taped & reeled of 1500pcs per reel (EIA-296, 10mm pitch, 63.5mm inside tape spacing).

**Power Cross Rating**

600VAC, 40A

**RoHS**

Comply with EU Directive 2011/65/EU, 2015/863.

**Reference Information 參考資料**

Current Rating 額定電流 (A)	Voltage Rating 額定電壓 (V)	Avg Cold Resistance 平均電阻 (ohm)	Avg V - drop 平均電壓降 (V)	Avg Power Dissipation 平均消耗功率 (W)	Average I <sup>2</sup> t value 熔化熱能 (A <sup>2</sup> sec)	Lightning surge 脈衝電流 (A)	cUL us	IEC
0.200	125/250	3.40	0.95	0.19	0.14	10	5R/5RP	5R/5RP 250V
0.250	125/250	2.55	0.85	0.21	0.25	15	5R/5RP	5R/5RP 250V
0.300	125/250	1.72	0.70	0.21	0.36	20	5R/5RP	5R/5RP 250V
0.350	125/250	1.22	0.60	0.21	0.60	25	5R/5RP	5R/5RP 250V
0.400	125/250	0.94	0.54	0.22	0.65	30	5R/5RP	5R/5RP 250V
0.500	125/250	0.60	0.44	0.22	1.1	35	5R/5RP	5R/5RP 250V
0.750	125/250	0.33	0.35	0.26	3.0	55	5R/5RP	5R/5RP 250V
1.0	125/250	0.18	0.27	0.27	6.2	*	5R/5RP	5R/5RP 250V
1.25	125/250	0.14	0.24	0.30	11	*	5R/5RP 125V	5R/5RP 250V
1.5	125/250	0.010	0.22	0.33	19	*	5R/5RP 125V	5R/5RP 250V
1.6	125/250	0.095	0.22	0.35	21	*	5R/5RP 125V	5R/5RP 250V
2.0	125/250	0.065	0.19	0.38	26	*	5R/5RP 125V	5R/5RP 250V
2.5	125/250	0.048	0.18	0.45	64	*	5R/5RP 125V	5R/5RP 250V
3.0	125/250	0.038	0.17	0.51	93	*	5R/5RP 125V	5R/5RP 250V
4.0	125/250	0.025	0.15	0.60	105	*	5R/5RP 125V	5R/5RP 250V
5.0	125/250	0.019	0.15	0.75	175	*	5R/5RP 125V	5R/5RP 250V

## Note (備註):

1. The Voltage Drop values are measured at 100% rated current.
2. The Power Dissipation values are measured after testing at 100% rated current.
3. The above figures are typical values for reference only and should not be used as acceptance criteria.
4. Please consult factory for availability of other ratings.

\* Consult factory 向工廠查詢

Specifications subject to change without notice